Vishvakarma

Mechanical Paver



Features :- * Diesel Power * Low Profile * Double Hydraulic System * Vibratory Screed

The Vishvakarma Asphalt Paver is a highly maneuverable paving machine designed to meet the requirements of those in need of a paver for road areas as well road resurfacing and construction. The Vishvakarma Asphalt Paver machine is easily adapted to small and large paving works. The paver is a diesel powered, double hydraulic machine with a low profile that allows the operator a better view of all functions.

The Vishvakarma Asphalt Paver is the most complete machine in its class and is the greatest value for the investment.

* Quality that you can rely upon *

Vishvakarma

Paver Finisher





SPECIFICATION

PERFORMANCE : Paving width : 2.5m-4.0m Paving thickness: Upto 200m Paving speed : 4-23 m/min Travel speed : 15 Km/h (Max)

Overall length: 5000 mm Overall width : 3000 mm Overall height: 2750 mm Wheel base : 2450 mm Wheel track : 1950 mm Weight

: 8500 Kgs. Approx)

Twin mechanical driven Abrasion resistant auger screw SCREED:

450mm. (L) x 2500mm(W) - 2Pcs

TANK CAPACITY:

Fuel tank: 100 Lts Hydraulic oil tank: 45 Lts.

Twin hydraulic operated folding hoppers of 4cu,mt.capacity (Approx.)

CONVEYOR (FEEDER):

Twin lane type 80mm pitch, mechanically drive

Front : solid rubber type wheel - 2 Nos. Rear: 11.00 x 20 - 16 Ply, 2 Nos.

450mm(L) x 150mm(W) x 2 Nos. 450mm(L) x 225mm(W) x 2 Nos. 450mm(L) x 300mm(W) x 2 Nos.

TAMPER (VIBRATOR):

Hydraulic Drive

Kirloskar model - 4 R 1040, 65 HP-1800 RPM water cooled 4 cylinders, Industrial engine.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE DUE TO DEVELOPMENT.

Manufacturers by:-



Vishvakarma Road Equipment Co (P) Limited.

Near, S. D. Chambers, Borsad - 388540, Gujarat (INDIA) Phone - 02696-21317, 21217, 23297, Fax - 22926

E- mail- vreco@ vishvakarma.com Website - www.vishvakarma.com